







MarksmanELITE

High Resolution InkJet Printing










MarksmanELITE

Dimensions:







Controller Specifications:

Touch Screen Display Operator Interface

QWERTY Keypad Enclosure Memory

Connectivity Processor Data Storage Power Input Operating System

Auto Codes

17" Color Touch Screen

Graphical User Interface, WYSIWYG Editor

Sealed Elastomer Stainless Steel

2 GB, 200 pin DDR2 SO-DIMM 4 USB, 2 RS232 Serial

Intel® Atom™ N2800 40 GB Solid State SATA drive 100-240VAC, 50-60Hz at 3A max Windows® Embedded Standard 7

Time, Date, Use By, Julian, Count, User

Defined Shifts, Variable Input

Bar Codes

I2of5, UPC A/E, Code 39, C93, 128,

Logos Fonts

Number of Printheads

Printhead to Controller

Environment

Operating Humidity

Data Matrix

Monochrome bit map files only Windows True Type fonts

Up to 4 768 or 384, Max two production lines, heads split in any configuration

Maximum distance between printhead and controller is 25 ft (7.6 meters) max

Ambient operating temperature: 40° to 104° F (5° to 40° C) 10-90%, non-condensing

Features and Benefits:



Color Touch Screen – 17" color graphical user interface guides users easily through menu functions.

Designed with fewer components - up to 50% less components than previous models maximizing reliability and uptime.

Less Power – utilizing Intel's low power Atom processor and Solid State Disk the Elite consumes a third less power compared to previous models.

Windows Based – allows for easy user interface and easy message creation.

Optional Keyless message selection allows user to easily select message for print.

Distributor Information:



Fastening/Supply: 800.513.9918

Packaging: 800.252.5894

LINCsystems.com

